

corner made 79. poles & 3 links South of the Southern half mile post & stone plandit.

corner made at the center of Section 31 T8 R1. E by planting a stone. corner made by planting a stone

corner made by planting a stone East of the center

corner made by planting a stone 80 poles $7\frac{1}{4}$ links east of the

X Southern $\frac{1}{2}$ mile post

length of the line South of the center 159. poles 23. links.

length of the line North of the center 160. poles 21. links

Coleman Carter and William Shields.

Chain Bearers: sworn

James W. Spencer

Monroe County Surveyor.

November 30th A.D. 1863.

ran the following lot of land for Charles Coor Mary Clarkston & James Sullivan beginning at the North East corner of Section No 25 T10 R1. W stone planted and witness three red oak 12 inches diameter S 67° E 26 links distand then South with the Meridian 79. poles & 9 links. ~~intercept~~ it being the intermediate distance between the North East corner of said Section No 25 to the Eastern $\frac{1}{2}$ mile of the same witness three Hickory 3. in dian N 48° E 40 links dist. then west 78 poles $1\frac{1}{2}$ links to a stake then North 79. poles & 9 links to a stake it being the intermediate distance between the North East corner of said Section No 25 to the Northern $\frac{1}{2}$ mile post of the same then East with the section line 78 poles $1\frac{1}{2}$ links to the beginning.

Chain bearers. Stephen Wilson & Liram A. Bastow
sworn

James W. Spencer

Monroe County Surveyor